
Bump'R Documentation

Release 0.3.7

Axel Haustant

Oct 29, 2017

Contents

1	Compatibility	3
2	Installation	5
3	Usage	7
4	Documentation	9
4.1	Workflow	9
4.2	Configuration file	10
4.3	Command line usage	12
4.4	Hooks	13
4.5	Changelog	16
5	Indices and tables	19

Bump'R is a version bumper and releaser allowing in a single command:

- Clean-up release artifact
- Bump version and tag it
- Build a source distribution and upload on PyPI
- Update version for a new development cycle

Bump'R intend to be customizable with the following features:

- Optionnal test suite run before bump
- Customizable with a config file
- Overridable by command line
- Extensible with hooks

The main goal is to provide a release workflow without manual intervention.

CHAPTER 1

Compatibility

Bump'R requires Python 2.6+

CHAPTER 2

Installation

You can install Bump'R with pip:

```
$ pip install bumpr
```

or with easy_install:

```
$ easy_install bumpr
```


CHAPTER 3

Usage

You can use directly the command line to setup every parameter:

```
$ bumprr fake/__init__.py README.rst -M -ps dev
```

But Bump'R is designed to work with a configuration file (`bumprr.rc` by defaults). Some features are only availables with the configuration file like:

- commit message customization
- hooks configuration
- multiline test, clean and publish commands

Here's an exemple:

```
[bumprr]
file = fake/__init__.py
vcs = git
tests = tox
publish = python setup.py sdist register upload
clean =
    python setup.py clean
    rm -rf *egg-info build dist
files = README.rst

[bump]
unsuffix = true
message = Bump version {version}

[prepare]
suffix = dev
message = Prepare version {version} for next development cycle

[changelog]
file = CHANGELOG.rst
bump = {version} ({date:%Y-%m-%d})
```

```
prepare = In development
```

```
[readthedoc]
```

```
id = fake
```

This way you only have to specify which part you want to bump on the command line:

```
$ bumpr -M -s rc4 # Bump the major with an 'rc4' suffix
```

```
$ bumpr          # Bump the default part aka. patch
```

Workflow

When you execute Bump'R it will follow the following workflow:

1. `clean`
2. `test`
3. `bump`
4. `publish`
5. `prepare`

If you have been using Maven, it's inspired by the Maven Release Plugin.

Clean phase

Optionnal phase that simply execute the commands provided by the `clean` configuration parameter.

Test phase

Optionnal phase that simply execute the commands provided by the `tests` configuration parameter.

Bump phase

This is the main phase in which Bump'R will:

1. Compute replacements
2. Execute the bump phase for each hook
3. Bump replacement in version file and extra files

4. Commit the changes if a VCS is configured with `commit=True`
5. Tag the previously created commit if `tag=True`

Publish phase

Optionnal phase that simply execute the commands provided by the `publish` configuration parameter.

Most of the time for Python project, you will want to execute:

```
python setup.py sdist register upload
```

Prepare phase

This is the second main phase in which Bump'R will:

1. Compute replacements
2. Execute the prepare phase for each hook
3. Bump replacement in version file and extra files
4. Commit the changes if a VCS is configured with `commit=True`

Configuration file

The `bump'r.rc` configuration file is an inifile with the following possible sections and keys.

Note: You can also use the `setup.cfg` file to store the configuration. It's recommended to prefix section with `bump'r:` (ie. `[bump'r:bump]`). Be carefull, when using Python 3, `setup.cfg` is parsed with `ConfigParser` and perform string interpolation.

bump'r

This is the main section defining the common behavior and parameters.

file *Default:* None

The file containing the version string to extract.

regex *Default:* `r'(__version__|VERSION)\s*=\s*(\'|")(?P<version>.+?)(\'|")'`

The regex used to extract the version string. It must have a `version` named group.

encoding *Default:* `utf8`

The files encoding.

vcs *Default:* None

commit *Default:* `True`

If `True` and `vcs` is defined, commit the changes.

push *Default:* `False`

If `True` and `vcs` is defined, push the changes and the tags to the upstream repository.

tag: *Default:* True

If True and vcs is defined, tag the version.

tag_format: *Default:* {version}

Specify the format of the tag

tag_annotation: *Default:* None

Specify an optional tag annotation formatted with the {version} token

verbose *Default:* False

If True, display verbose output and command line output.

dryrun *Default:* False

If True, no command or VCS operation will be executed. They will be displayed in the command output.

clean *Default:* None

Specify the commands to be executed on the *clean* phase. Should have a single command by line.

tests *Default:* None

Specify the commands to be executed on the *test* phase. Should have a single command by line.

publish *Default:* None

Specify the commands to be executed on the *publish* phase. Should have a single command by line.

files *Default:* []

Extra files to process. Those files will be processed by hooks to. Specify one file by line.

bump

This section define the bump phase behavior.

unsuffix *Default:* True

If True the current verion suffix will be removed.

suffix: *Default:* None

If set, this suffix will ba appended to the version.

part: *Default:* None

Specify the part to bump between major, minor or patch.

message *Default:* Bump version {version}

Specify the commit message that will be bumped. You can use the following token in your format pattern: version, major, minor, patch and date. All formating operations are accepted.

prepare

This section define the prepare phase behavior.

unsuffix *Default:* False

If True the current verion suffix will be removed.

suffix: *Default:* None

If set, this suffix will be appended to the version.

part: *Default:* patch

Specify the part to bump between major, minor or patch.

message *Default:* Update to version {version} for next development cycle

Specify the commit message that will be bumped. You can use the following token in your format pattern: version, major, minor, patch and date. All formatting operations are accepted.

hooks

Each hook can contribute to configuration with its own section.

See *Hooks*.

sample

Here a sample `bump.r.rc` file

```
[bump]
file = fake/__init__.py
vcs = git
tests = tox
publish = python setup.py register sdist upload
clean =
    python setup.py clean
    rm -rf *egg-info build dist
files = README.rst

[bump]
message = 'Commit version {version}'

[prepare]
suffix = dev
message = Prepare version {version} for next development cycle

[changelog]
file = CHANGELOG.rst
bump = {version} ({date:%Y-%m-%d})
prepare = In development

[readthedoc]
id = bump
```

Command line usage

The bump'r executable can be used in two ways:

- one shot usage with all parameters on command line
- regular usage with most of the parameters in a configuration file

The default configuration file name is `bump.r.rc` but you can override it with the `-c` option.

All mandatory parameters not present in the configuration file should be on command line.

```
$ bump -h
usage: bump [-h] [--version] [-v] [-c CONFIG] [-d] [-st] [-b | -pr] [-M] [-m]
            [-p] [-s SUFFIX] [-u] [-pM] [-pm] [-pp] [-ps PREPARE_SUFFIX]
            [-pu] [--vcs {git,hg}] [-nc] [-P] [-nP]
            [file] [files [files ...]]

Version bumper and Python package releaser

positional arguments:
  file                Versionned module file
  files               Files to update

optional arguments:
  -h, --help          show this help message and exit
  --version            show program's version number and exit
  -v, --verbose        Verbose output
  -c CONFIG, --config CONFIG
                      Specify a configuration file
  -d, --dryrun         Do not write anything and display a diff
  -st, --skip-tests    Skip tests
  -b, --bump           Only perform the bump
  -pr, --prepare       Only perform the prepare

bump:
  -M, --major          Bump major version
  -m, --minor          Bump minor version
  -p, --patch          Bump patch version
  -s SUFFIX, --suffix SUFFIX
                      Set suffix
  -u, --unsuffix       Unset suffix

prepare:
  -pM, --prepare-major Bump major version
  -pm, --prepare-minor Bump minor version
  -pp, --prepare-patch Bump patch version
  -ps PREPARE_SUFFIX, --prepare-suffix PREPARE_SUFFIX
                      Set suffix
  -pu, --prepare-unsuffix
                      Unset suffix

Version control system:
  --vcs {git,hg}       VCS implementation
  -nc, --nocommit      Do not commit
  -P, --push           Push changes to remote repository
  -nP, --no-push       Don't push changes to remote repository
```

Hooks

Read the doc

This hook allow to change the Read The Doc documentation URL in both bump and prepare phase.

- **key:** readthedoc
- **parameters**
 - id: None
 - url: `http://{id}.readthedocs.org/en/{tag}`
 - bump: {version}
 - prepare: latest

Most of the the time, you will just have to specify your readthedoc project identifier.

```
[readthedoc]
id = myproject
```

You can customize the generated (and parsed) URL and the string to bump in.

```
[readthedoc]
url = http://custom.doc/{tag}
```

You can also customize the tag part in the url for the bump and prepare phase

```
[readthedoc]
bump = {version}
prepare = latest
```

Changelog

This hook allow to bump and prepare your changelog. In the bump phase it will bump the current developpement header with a versionned one. In the prepare phase, it will do the inverse operation.

- **key:** changelog
- **parameters**
 - file: None
 - separator: -
 - bump: {version} ({date:%Y-%m-%d}) '
 - prepare: Current
 - empty: Nothing yet

The file parameter is mandatory and designate the changelog file.

The separator parameter spcify the character user to underline your changelog section.

```
Changelog
=====

In development
~~~~~

- Another feature

Version 1.0.1 (2013-08-23)
~~~~~
```

```
- Some new feature
```

To handle this changelog you will have the following configuration

```
[changelog]
file = CHANGELOG
separator = ~
bump = Version {version} ({date:%Y-%m-%d})
prepare = In development
empty = Empty
```

If you execute Bump'R, the changelog will be bumped like:

```
Changelog
=====

Version 1.0.2 (2013-08-24)
~~~~~

- Another feature

Version 1.0.1 (2013-08-23)
~~~~~

- Some new feature
```

And then prepared:

```
Changelog
=====

In development
~~~~~

- Empty

Version 1.0.2 (2013-08-24)
~~~~~

- Another feature

Version 1.0.1 (2013-08-23)
~~~~~

- Some new feature
```

Commands

This hook allow to execute custom commands during bump and prepare phases.

- **key:** commands
- **parameters**
 - bump: {version}
 - prepare: latest

Both bump and prepare command can be multiline (a command statement by line), and support the following format token:

- **version**: the current phase version string
- **major**: the current phase version major part
- **minor**: the current phase version minor part
- **patch**: the current phase version patch part
- **date**: the current date (aka. the release date)

In the bump phase, version will be the bumped version whereas in the prepare phase it will be the prepared/next version.

Exemple:

```
[commands]
bump = echo "{major}.{minor} - {date:%Y-%m-%d} "
prepare = echo "Next version: {version}"
```

Changelog

0.3.7 (2017-10-29)

- Drop support for Python 2.6 and 3.3
- Properly display dry run prepare diff
- Warn only for dirty workspace on dry run
- Optional tag annotation support

0.3.6 (2017-01-10)

- Make use of custom *tag_format* in readthedoc hook
- Expose *{tag}* in replace and command hook
- Expose *{tag}* in commit messages

0.3.5 (2017-01-10)

- Allow to specify a custom tag pattern

0.3.4 (2017-01-10)

- Added *-st/-skip-tests* option

0.3.3 (2017-01-08)

- Push action is verbose

0.3.2 (2017-01-08)

- Fix some boolean handling from commandline

0.3.1 (2017-01-08)

- Ensure push is executed
- Fix boolean parsing
- Fix error handling on version extraction

0.3.0 (2017-01-08)

- Support separator omission in changelog (for markdown)
- Add readthedoc badge support.
- **Breaking** Use https and readthedocs.io as default
- *setup.cfg* declaration support
- Optionnal *bump'r*: prefix support
- Switch to pytest

0.2.1 (2015-11-21)

- Use nosetests instead of custom discovery
- Some fixes on Python 3 (mostly encodings)
- Improve error handling
- Validate configuration

0.2.0 (2013-08-24)

- colored diff
- Added `--bump` and `--prepare` to only perform bump or prepare
- Rely on VCS for tracking files and ensure working copy is clean
- Added option `--nocommit`
- Ensure dry run does not write or execute anything
- Better output and error handling
- Group parameters in help
- Added optionnal hook validation
- Fix some Python incompatibilities (Python 2.6 and 3.X)
- More documentation

0.1.0 (2013-08-22)

- Initial release. Missing some parts but working!

CHAPTER 5

Indices and tables

- `genindex`
- `modindex`
- `search`